



GDVAL DIN Gate valve.

Size	F5						
	PN10						
	Operated Torque(N*m)	Turns to open or Close	ISO Top flange mounting	Body gasket(mm)	Packing size(mm)	Packing Qty	Stem diameter
DN40	35	13	F7	Ø94XØ81XØ75X4.5	Ø18X5	7	Tr18×4-LH
DN50	45	16	F7	Ø108XØ96XØ90X4.5	Ø20X6.5	7	Tr20×4-LH
DN65	65	16	F7	Ø139XØ128XØ120X4.5	Ø24X8	7	Tr24×5-LH
DN80	75	18	F7	Ø149XØ138XØ130X4.5	Ø24X8	7	Tr24×5-LH
DN100	87	25	F7	Ø177XØ162XØ154X4.5	Ø26X8	7	Tr26×5-LH
DN125	130	29	F10	Ø204XØ190XØ182X4.5	Ø26X7	7	Tr26×5-LH
DN150	170	35	F10	Ø234XØ218XØ210X4.5	Ø28X8	7	Tr28×5-LH
DN200	220	38	F10	Ø289XØ273XØ265X4.5	Ø32X10	7	Tr32×6-LH
DN250	250	47	F14	Ø349XØ330XØ320X4.5	Ø36X10	7	Tr36×6-LH
DN300	300	47	F14	Ø424XØ402XØ390X4.5	Ø40X10	10	Tr40×7-LH
DN350	350	54	F14	Ø483XØ454XØ440X4.5	Ø40X10	10	Tr40×7-LH
DN400	500	62	F14	Ø523XØ498XØ485X4.5	Ø44X10	10	Tr44×7-LH
DN500	650	68	F16	Ø638XØ612XØ600X4.5	Ø50X10	10	Tr50×8-LH
DN600	950	71	F25	Ø748XØ716XØ700X4.5	Ø60X12.5	10	Tr60×9-LH

Size	F5						
	PN25						
	Operated Torque(N*m)	Turns to open or Close	ISO Top flange mounting	Body gasket(mm)	Packing size(mm)	Packing Qty	Stem diameter
DN40	40	13	F7	Ø94XØ81XØ75X4.5	Ø18X5	7	Tr18×4-LH
DN50	50	16	F7	Ø108XØ96XØ90X4.5	Ø20X6.5	7	Tr20×4-LH
DN65	70	16	F7	Ø139XØ128XØ120X4.5	Ø24X8	7	Tr24×5-LH
DN80	80	18	F7	Ø149XØ138XØ130X4.5	Ø24X8	7	Tr24×5-LH
DN100	100	25	F7	Ø177XØ162XØ154X4.5	Ø26X8	7	Tr26×5-LH
DN125	150	29	F10	Ø204XØ190XØ182X4.5	Ø26X7	7	Tr26×5-LH
DN150	200	35	F10	Ø234XØ218XØ210X4.5	Ø28X8	7	Tr28×5-LH
DN200	300	38	F10	Ø289XØ273XØ265X4.5	Ø32X10	7	Tr32×6-LH
DN250	350	47	F14	Ø349XØ330XØ320X4.5	Ø36X10	7	Tr36×6-LH
DN300	450	47	F14	Ø424XØ402XØ390X4.5	Ø40X10	10	Tr40×7-LH
DN350	500	54	F14	Ø483XØ454XØ440X4.5	Ø40X10	10	Tr40×7-LH
DN400	600	62	F14	Ø523XØ498XØ485X4.5	Ø44X10	10	Tr44×7-LH
DN500	800	68	F16	Ø638XØ612XØ600X4.5	Ø50X10	10	Tr50×8-LH
DN600	1300	71	F25	Ø748XØ716XØ700X4.5	Ø60X12.5	10	Tr60×9-LH



GDVAL DIN Gate valve.

Size	F5 PN16						
	Operated Torque(N*m)	Turns to open or Close	ISO Top flange mounting	Body gasket(mm)	Packing size(mm)	Packing Qty	Stem diameter
DN40	38	13	F7	Ø94XØ81XØ75X4.5	Ø18X5	7	Tr18×4-LH
DN50	48	16	F7	Ø108XØ96XØ90X4.5	Ø20X6.5	7	Tr20×4-LH
DN65	68	16	F7	Ø139XØ128XØ120X4.5	Ø24X8	7	Tr24×5-LH
DN80	78	18	F7	Ø149XØ138XØ130X4.5	Ø24X8	7	Tr24×5-LH
DN100	90	25	F7	Ø177XØ162XØ154X4.5	Ø26X8	7	Tr26×5-LH
DN125	140	29	F10	Ø204XØ190XØ182X4.5	Ø26X7	7	Tr26×5-LH
DN150	180	35	F10	Ø234XØ218XØ210X4.5	Ø28X8	7	Tr28×5-LH
DN200	250	38	F10	Ø289XØ273XØ265X4.5	Ø32X10	7	Tr32×6-LH
DN250	300	47	F14	Ø349XØ330XØ320X4.5	Ø36X10	7	Tr36×6-LH
DN300	350	47	F14	Ø424XØ402XØ390X4.5	Ø40X10	10	Tr40×7-LH
DN350	400	54	F14	Ø483XØ454XØ440X4.5	Ø40X10	10	Tr40×7-LH
DN400	550	62	F14	Ø523XØ498XØ485X4.5	Ø44X10	10	Tr44×7-LH
DN500	700	68	F16	Ø638XØ612XØ600X4.5	Ø50X10	10	Tr50×8-LH
DN600	1050	71	F25	Ø748XØ716XØ700X4.5	Ø60X12.5	10	Tr60×9-LH

Size	F7 PN40						
	Operated Torque(N*m)	Turns to open or Close	ISO Top flange mounting	Body gasket(mm)	Packing size(mm)	Packing Qty	Stem diameter
DN40	40	13	F7	Ø94XØ81XØ75X4.5	Ø18X5	7	Tr18×4-LH
DN50	50	16	F7	Ø108XØ96XØ90X4.5	Ø20X6.5	7	Tr20×4-LH
DN65	80	16	F7	Ø139XØ128XØ120X4.5	Ø24X8	7	Tr24×5-LH
DN80	100	18	F7	Ø149XØ138XØ130X4.5	Ø24X8	7	Tr24×5-LH
DN100	130	25	F7	Ø177XØ162XØ154X4.5	Ø26X8	7	Tr26×5-LH
DN125	200	29	F10	Ø204XØ190XØ182X4.5	Ø26X7	7	Tr26×5-LH
DN150	250	35	F10	Ø234XØ218XØ210X4.5	Ø28X8	7	Tr28×5-LH
DN200	300	38	F10	Ø289XØ273XØ265X4.5	Ø32X10	7	Tr32×6-LH
DN250	350	47	F14	Ø349XØ330XØ320X4.5	Ø36X10	7	Tr36×6-LH
DN300	500	47	F14	Ø429XØ400XØ390X4.5	Ø44X10	10	Tr44×7-LH
DN350	600	48	F14	Ø492XØ455XØ430X4.5	Ø46X9.5	10	Tr46×8-LH
DN400	750	54	F14	Ø515XØ485XØ470X4.5	Ø46X10	10	Tr46×8-LH
DN500	1000	68	F16	N/A	N/A	N/A	
DN600	1700	71	F25	Ø748XØ716XØ700X4.5	Ø60X12.5	10	Tr60×9-LH