



250	650	250	450	385	345	38	3	12-33	745	450
200	550	200	375	320	285	34	3	12-30	630	400
150	450	150	300	250	218	28	3	8-26	530	400
DN	L	d	D	C	g	b	f	n-ø	H	W

PARTS & MATERIAL LIST

ITEM	PART NAME	MATERIAL
1	Body	GS-25N+1.4024
2	Wedge Disc	GS-25N+1.4024
3	Stem	1.4024
4	Gasket	304+Graphite
5	Stud Bolt	B7
6	Nut	2H
7	Bonnet	GS-25N
8	Yoke Sleeve	GGG-40
9	Stuffing Box	GS-25N
10	Stud Bolt	CK35V
11	Nut	C35N
12	Gasket	304L+Graphite
13	Gland Forging	GS-25N
14	Gasket	304
15	Gland Packing	PTFE
16	Pin	35
17	Stud Bolt	CK35V
18	Nut	C35N
19	Washer	C1020
20	Washer	C1020
21	Lock Nut	25
22	Hand Wheel	GGG-40

Note:

- 1.Design and machining in accordance with DIN3352
- 2.Inspection and test in accordance with DIN3230-T3
- 3.Face to face dimension in accordance with DIN3202
- 4.Dimension of connection end flange in accordance with DIN2545

DN150~250 PN40 GATE VALVE NRS

CLIENT		DWG REV .NO	00
P.O.NO		CLASS	
APPROVED BY		HYDROSTATIC TEST (PSI)	SHELL SEAT
REVIEWED BY			
MADE BY		AIR TSET	
DRAWING NO	286	DATE	

GDVAL VALVE