


DN125~150



Medium flow direction: From up hole to down hole

### PARTS & MATERIAL LIST

ITEM	PART NAME	MATERIAL
1	Body	GS-C25N
2	Disc	410
3	Stem	410
4	Disc Gland	410
5	Gasket	304+Graphite
6	Bonnet	GS-C25N
7	Stud Bolt	24CRMO5
8	Nut	CK35
9	Gland Packing	Graphite
10	Gland Forging	GS-C25N
11	Stud Bolt	24CRMO5
12	Nut	CK35
13	Pin	C1035
14	Yoke Sleeve	GGG40
15	Hand Wheel	GGG40
16	Washer	C1035
17	Lock Nut	C1035
18	Ring	410
19	Inter Disc	410

150	480	218	250	300	28	3	8-26	465	300
125	400	188	220	270	26	3	8-26	415	250
100	350	162	190	235	24	3	8-22	360	225
80	310	138	160	200	24	3	8-18	300	200
65	290	122	145	185	22	3	8-18	275	180
50	230	102	125	165	20	3	4-18	240	160
40	200	88	110	150	18	3	4-18	230	160
32	180	78	100	140	18	2	4-18	205	140
25	160	68	85	115	18	2	4-14	200	140
20	150	58	75	105	18	2	4-14	192	120
15	130	45	65	95	16	2	4-14	190	120
DN	L	g	C	D	b	f	n-ø	H	W

#### Note:

- 1.Design and machining in accordance with DIN3356
- 2.Inspection and test in accordance with DIN3230-T3
- 3.Face to face dimension in accordance with DIN3202-F1
- 4.Dimension of connection end flange in accordance with DIN2544

### DN15~150 PN25 GLOBE VALVE

CLIENT		DWG REV .NO	00
P.O.NO		CLASS	
APPROVED BY		HYDROSTATIC TEST (PSI)	SHELL SEAT
REVIEWED BY			
MADE BY		AIR TSET	
DRAWING NO	360	DATE	

GDVAL VALVE