



Medium flow direction: From up hole to down hole

PARTS & MATERIAL LIST

ITEM	PART NAME		MATERIAL	
1	Body		1.0619	
2	Disc		1.4006	
3	Stem		1.4006	
4	Disc Gland		1.4006	
5	Gasket		1.4301+Graphite	
6	Bonnet		1.0619	
7	Stud Bolt		G	
8	Nut		YK	
9	Gland Packing		Graphite	
10	Gland Forging		1.0619	
11	Stud Bolt		G	
12	Nut		YK	
13	Pin		1.0501	
14	Yoke Sleeve		GGG40	
15	Hand Wheel		GGG40	
16	Washer		1.0501	
17	Lock Nut		1.0503	
18	Ring		1.4006	
19	Inter Disc		1.4006	

300	850	378	410	460	28	4	12-26	820	600
250	730	320	355	405	26	3	12-25	680	500
200	600	268	295	340	24	3	12-22	540	400
150	480	212	240	285	22	3	8-22	465	300
125	400	188	210	250	22	3	8-18	415	250
100	350	158	180	220	20	3	8-18	360	225
80	310	138	160	200	20	3	8-18	300	200
65	290	122	145	185	18	3	4-18	275	180
50	230	102	125	165	20	3	4-18	240	160
40	200	88	110	150	18	3	4-18	230	160
32	180	78	100	140	18	2	4-18	205	140
25	160	68	85	115	18	2	4-14	200	140
20	150	58	75	105	18	2	4-14	192	120
15	130	45	65	95	16	2	4-14	190	120
DN	L	g	C	D	b	f	n-φ	H	W

Note:

- 1.Design and machining in accordance with DIN3356
- 2.Inspection and test in accordance with DIN3230-T3
- 3.Face to face dimension in accordance with DIN3202-F1
- 4.Dimension of connection end flange in accordance with DIN2543

DN15~300 PN16 GLOBE VALVE

CLIENT		DWG REV .NO	00
P.O.NO		CLASS	
APPROVED BY		HYDROSTATIC TEST (PSI)	SHELL SEAT
REVIEWED BY			
MADE BY		AIR TSET	
DRAWING NO	352	DATE	

GDVAL VALVE