

NOTES:

1 MATERIAL STANDARD:DIN 2 HYDRO-TEST:DIN 3230

3 END FLANGE DIMENSIONS:DIN 2543

Performance Specification						
No	1.6					
Test Pressure	Intensity test	2.4				
	Back seal test		MPa			
	Seal test					
	Gas test	\				
Worl	°C					
Medium: water oil & gas						

STRAINER-"T" TYPE PN16								
CLIENT		DWG REV .N□	00					
P.O.NO		CLASS						
APPROVED BY		HYDROSIATIC	SHELL					
REVIEWED BY	REVIEWED BY		SEAT					
MADE BY		AIR TSET						
DRAWING NO	GLQ-T-1-1.4408	DATE						
GDVAL VALVE								

PN DN L H 50 230 115 65 260 130 80 280 140 100 350 175 125 400 200 150 450 225 200 500 250 200 590 295 300 680 340 350 790 395 400 850 425				6 5 4 3 2	Ξ
16	PN	DN	L	Н	
65 260 130 80 280 140 100 350 175 125 400 200 150 450 225 200 500 250 250 590 295 300 680 340 350 790 395					
100 350 175 125 400 200 150 450 225 200 500 250 250 590 295 300 680 340 350 790 395		65	260	130	
125 400 200 150 450 225 200 500 250 250 590 295 300 680 340 350 790 395		80	280	140	
150		100	350	175	
16 200 500 250 250 590 295 300 680 340 350 790 395		125	400	200	
16 250 590 295 300 680 340 350 790 395		150			
300 680 340 350 790 395					
350 680 340 350 790 395	16				
	'				
400 850 425					
450 900 450					
500 1000 500					
600 1200 600		600	1200	600	